


blade-tightening device



Hydraulic vertical hold-downs that manually slide on prismatic guides (optional)



Powered device for the rotation of the saw

KATANA STAND ALONE BAND SAWS

MODEL		K 60	K 100	K 115	K 126 F	K 126	K 206	K 258
Sawing Capacity 90°	mm	610x310	1015x450	1100x510	1250x600	1250x600	2000x600	2540x815
Saw Mitering	Degrees	± 60°	± 60°	± 60°	no mitering	± 60°	± 45°	± 45°
Blade dimensions	mm	34 x 1.1	41 x 1.3	54 x 1.3	67 x 1.6	67 x 1.6	67 x 1.6	67 x 1.6
Motor power	kW	7	9	15	15	15	15	18

KATANA CN BAND SAWING SYSTEMS

MODEL		K 60L	K 100L	K 115L	K 126L	K 206L	K 258L
Sawing Capacity 90°	mm	610x310	1015x450	1100x510	1250x600	2000x600	2540x815
Saw Mitering	Degrees	± 60°	± 60°	± 60°	± 60°	± 45°	± 45°
Blade dimension	mm	34 x 1.1	41 x 1.3	54 x 1.3	67 x 1.6	67 x 1.6	67 x 1.6
Motor power	kW	7	9	15	15	15	18
CNC Axes	no.	3	3	3	3	3	2