

- High speed and precision
- Environmentally clean by using no hydraulic fluid
- Extreme reliability and quality
- Quiet operation

Model		BB4013
Bending Length: in (mm)	A	49.6 (1260)
Bending Capacity: US tons (metric tons)		40 (36)
Stroke: in (mm)	I	5.9 (150)
Max Approach Speed: in/s (mm/s)		3.9 (100)
Max Bend Speed: in/s (mm/s)		0.8 (20)
Max Return Speed: in/s (mm/s)		3.9 (100)
Back Gauge Stroke: in (mm)		25.6 (650)
Max Back Gauge Stop Distance: in (mm)		31.5 (800)
Throat Depth: in (mm)	G	3.9 (100)
Open Height: in (mm)	D	11 (280)
Distance between Frames: in (mm)	B	51.2 (1300)
Table width: in (mm)	C	3.9 (100)
Table height: in (mm)	E	35.4 (900)
Total width: in (mm)	L	65.3 (1660)
Total depth: in (mm)	J	72.8 (1850)
Total Height: in (mm)	H	93.7 (2380)
Electrical Cabinet Swing depth: in (mm)	K	24.4 (620)
Control Arm Swing Area: in (mm)		45.3 (1150)
Oil Tank: gal (ltr)		None
Machine Weight: lb (kg)		7,716 (3,500)
Full Load Amps @ 480V (X,R,Z1,Z2,AC)		46 @ 208 V