

- The parallelism of this machine is achieved by synchronizing the hydraulic cylinders using an advanced proportional control valve
- Automatic indexing of the axes at the start of the running process
- Manual, semi-automatic and automatic working mode

Model #	Bending Length in (mm)	Bending Capacity US tons (metric tons)	Stroke (mm)	Max Approach Speed in/s (mm/s)
DSXL 100-26	102.4 (2600)	110 (100)	11.8 (300)	6.3 (160)
DSXL 100-30	118.9 (3020)	110 (100)	11.8 (300)	6.3 (160)
DSXL 135-26	102.4 (2600)	149 (135)	12.6 (320)	6.3 (160)
DSXL 135-30	118.9 (3020)	149 (135)	12.6 (320)	6.3 (160)
DSXL 135-36	141.7 (3600)	149 (135)	12.6 (320)	6.3 (160)
DSXL 135-40	159.4 (4050)	149 (135)	12.6 (320)	6.3 (160)
DSXL 175-30	118.9 (3020)	193 (175)	13.8 (350)	5.9 (150)
DSXL 175-36	141.7 (3600)	193 (175)	13.8 (350)	5.9 (150)
DSXL 175-40	159.4 (4050)	193 (175)	13.8 (350)	5.9 (150)
DSXL 220-30	118.9 (3020)	242 (220)	13.8 (350)	5.5 (140)
DSXL 220-36	141.7 (3600)	242 (220)	13.8 (350)	5.5 (140)
DSXL 220-40	159.4 (4050)	242 (220)	13.8 (350)	5.5 (140)
DSXL 220-60	238.2 (6050)	242 (220)	13.8 (350)	3.9 (100)
DSXL 320-30	118.9 (3020)	352 (320)	15.7 (400)	5.5 (140)
DSXL 320-36	141.7 (3600)	352 (320)	15.7 (400)	5.5 (140)
DSXL 320-40	159.4 (4050)	352 (320)	15.7 (400)	5.5 (140)
DSXL 320-60	238.2 (6050)	352 (320)	15.7 (400)	3.1 (80)
DSXL 40-15	61.0 (1550)	44 (40)	8.7 (220)	7.1 (180)
DSXL 400-40	159.4 (4050)	440 (400)	15.7 (400)	3.1 (80)
DSXL 400-60	238.2 (6050)	440 (400)	15.7 (400)	2.4 (60)
DSXL 500-60	238.2 (6050)	550 (500)	15.7 (400)	2.4 (60)
DSXL 60-20	80.7 (2050)	66 (60)	8.7 (220)	7.1 (180)
DSXL 600-60	238.2 (6050)	660 (600)	16.9 (430)	2.4 (60)