

## Machine Specifications

- Capacity 40" High x 40" Wide x 35" Length
- Weight Capacity 10,000 lbs
- Blade Speed 330-2000 SFPM
- Blade Size 1¼" X .040" X 25' (35-40 Grit)
- Blade Guide High Speed Rollers
- Blade Tension Automatic Preset, Hydraulic
- Vise Vertical Hold down
- Blade Drive 10 HP, AC Vector Drive
- Sawing Force Ball Screw Positive Down feed
- Coolant Capacity 20 Gallons
- Hydraulic Capacity 20 Gallons
- Hydraulic Drive 5 HP Motor
- Work Height 112"
- Shipping Weight 7,500 lbs
- Electrics Fused Disconnect, 115 Volt Controls
- Table Dimensions 30" High Saw Bed/Fixture
- 36" Deep (35" Cut)
- 30" Wide
- 30" From Blade to Front of Worktable
- Ship Dimensions Across Front – 13' 6"
- Front to Back – 66"
- Height – 112"
- \*Specifications subject to change without notice

## Voltage

208-60-3, 230-60-3, 460-60-3, 575-60-3

## Optional Accessories

- 1¼" Diamond Segmented Blade
- Laser Shadow Line
- Vertical Support Plate for Top Cap of Ingot
- Ball Screw Positive Down feed
- High Speed Option, 330-2000 SFPM
- All Motors and Controls Fused Disconnect
- Broken Blade Automatic Shutoff
- Console Controlled Blade Speed w/ Digital Indicator
- AC Vector Drive
- Hydraulic Blade Tension with Indicator
- Electronic Door Safety Interlocks
- Operator Manual and Parts List
- Special Full Stroke Hydraulic Hold down V-Configuration with Removable V-Block Holder

More models available!

1.866.995.9910