

**W.F. WELLS - MODEL B-25-3A3 CNC, Large Capacity Horizontal Twin Column CNC Shuttle Barfeed Bandsaw**

**Specifications**

Capacity..... 25" High x 40" Wide, 25.5" Round  
 Weight Capacity..... 14,000 lbs  
 Blade Speed ..... 60-500 SFPM  
 Blade Size ..... 2" X .063" X 26'-6", 2<sup>5</sup>/<sub>8</sub> optional  
 Blade Guide..... Spring Tensioned Carbide Blocks with Idle Roller Back-up  
 Blade Tension..... Hydraulic  
 Bandwheel Size ..... 26"  
 Vise ..... Hydraulic  
 Blade Drive ..... 15 HP, AC Vector Drive  
 Sawing Force..... 0-1,000 lbs  
 Coolant Capacity ..... 15 Gallons  
 Hydraulic Capacity ..... 20 Gallons  
 Hydraulic Drive ..... 5 HP Motor  
 Work Height..... 35"  
 Outfeed Table ..... 12" X 41"  
 Vise Jaw Height ..... 17"  
 Barfeed Projection ..... 0 - 36" CNC Controlled  
 Projection Accuracy ..... +/- .002"  
 Shuttle Indexes ..... Unlimited  
 Remnant End..... 14"  
 Shipping Weight..... 11,400 lbs  
 Electrics ..... Wired to NFPA 79 Machine Tool Standards  
 Linear Rail Frame Traverse  
 Hydraulic Positioned Guide Arm, Powered Blade Brush, Blade Break/Stall Switch  
 CNC Programmable Controlled with Color Touch Screen  
 500+ Job Selection  
 Automatic Kerf Compensation  
 Shipping Weight.....11,400  
 Shipping Dimensions.....170"L x 102"W x 105"H

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

Discharge Worktable, 40" Wide x 56" Long  
 Hydraulic Chip Conveyor  
 Hydraulic Holddown, Saw Vise  
 Hydraulic Holddown, Barfeed Vise  
 Outboard Vise with Hydraulic Holddown  
 Outboard Vise  
 Non-Powered Conveyor 36" x 5'  
 Non-Powered Conveyor 36" x 10'  
 40" Conveyor  
 High Speed Drive & Guides (1½" Blade) 500-3000 SFPM

**More models available.**