## W.F. WELLS - MODEL M-36-3, Large Capacity Horizontal Cant Head Twin Column Two Direction Miter Saw

**Specifications**

| | |
|---|---|
| Capacity | 22" H X 48" W @ 90°, 22" H X 36" W @ - 45°<br>22" H X 31½ W @ + 45° |
| Frame Cant | 6° |
| Weight Capacity | 15,000 lbs |
| Blade Speed | 60-500 SFPM |
| Blade Size | 2" X .063" X 28' 6" |
| Blade Guide | Spring Tensioned Carbide Blocks with Idle Roller Backup |
| Blade Tension | Hydraulic |
| Bandwheel Size | 26" |
| Vise | Hydraulic |
| Blade Drive | 15 HP, AC Vector Drive |
| Sawing Force | 0-1,000 lbs |
| Coolant Capacity | 15 Gallons |
| Hydraulic Capacity | 20 Gallons |
| Hydraulic Drive | 5 HP Motor |
| Work Height | 34" |
| Outfeed Table | 7" X 52" |

Linear Rail Frame Traverse
Hydraulic Positioned Guide Arm
Hydraulic Powered Blade Brush
Hydraulic Holddown, Saw Vise
Hydraulic Swivel Base with Miter Vise
Digital Angle Display
In Feed Roller
Free Standing Control Console
Blade Break/Stall Switch
Electronic Door Interlocks

| | |
|---|---|
| Shipping Weight | 12,000 |
| Shipping Dimensions | 200”L x 98”W x 105”H |
| Electrics | Wired to NFPA 79 Machine Tool Standards |

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

Hydraulic Chip Conveyor, Auger Style
Free Standing Outboard Vise
Hydraulic Powered Conveyor 36" X 10'
Laser Shadow Line
Non-Powered Conveyor 36" X 5'
Non-Powered Conveyor 36" X 10'

**More models available.**