

W.F. WELLS - MODEL W-9-1, Horizontal Twin Post Semi Automatic Bandsaw

Specifications

Capacity.....	Rectangular at 90° 9" High x 17" Wide, Round at 90° 9" Dia. Rectangular at 45° 9" High X 8" Wide, Round at 45° 8" Dia.
Weight Capacity.....	2,000 lbs
Blade Speed	70-380 SFPM
Blade Size	1" X .035" X 11'-6"
Sawing Feed.....	Variable, Hydraulic
Blade Guide.....	Carbide with Backup Rollers
Blade Tension.....	Manual
Bandwheel Size	14½"
Vise	Manual
Blade Drive	3HP, 3ph, 1½ HP, 1ph
Sawing Force.....	30-120 lbs
Coolant Capacity	10 Gallons
Hydraulic Capacity.....	¾ Gallon Capacity
Hydraulic Drive	1/3 HP Motor
Work Height.....	26"
Shipping Weight.....	990 lbs
Electrics	Wired to NFPA 79 Machine Tool Standards
Machine Dimensions.....	43" Length x 81" Width x 63" Height

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Casters (changes work height to 29-1/2")
 Automatic Length Stop Assembly
 Discharge Table, 20" W x 48" L (with Length Stop Assy)
 Work Light, Wired In
 Blade Tension Indicator
 Manual Air Vise
 Air Holddown
 Air Vise/Holddown Combined
 Blade Break/Stall Switch
 Stock Stand, 6" Roller
 Stock Stand, 12" Roller
 AC Vector Drive
 Free Standing Roller Stock Conveyors, 6" Centers
 18" X 5' X 2,500 lbs Cap. Distributed Weight
 18" X 10' X 5,000 lbs Cap. Distributed Weight

More models available.

W.F. WELLS - MODEL F-16-1, Horizontal Twin Post Semi Automatic Bandsaw

Specifications

Capacity	Rectangular at 90° 16" High x 20" Wide, Round at 90° 16" Diameter Rectangular at 45° 16" High X 10" Wide, Round at 45° 10" Diameter
Weight Capacity	5,000 lbs
Blade Speed	60-425 SFPM
Blade Size	1¼" X .042" X 15'
Sawing Feed	Variable, Hydraulic
Blade Guide	Rollers and Carbide Side Blocks
Blade Tension	Manual with Indicator
Bandwheel Size	20"
Vise	Manual, 8-1/2"
Blade Drive	7½ HP, 3ph, AC Vector Drive
Sawing Force	30-120 lbs
Coolant Capacity	15 Gallons
Hydraulic Capacity	¾ Gallon
Hydraulic Drive	½ HP Motor
Work Height	26"
Shipping Weight	2,100 lbs
Electrics	Wired to NFPA 79 Machine Tool Standards
Machine Dimensions	49" Length x 97" Width x 83" Height

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Automatic Length Stop Assembly
- Discharge Worktable, 20" W x 48" L with Stock Stop
- Work Light, Wired In
- Air Vise, Manual
- Air Holddown
- Air Vise/Holddown Combined
- Blade Break/Stall Switch
- Chip Conveyor, Electric Auger Style
- 21" x 10' Powered Conveyor, Electric
- High Speed Drive & Guides (1" Blade) 400-3000 SFPM
- Free Standing Roller Stock Conveyors, 6" Centers
- 18" X 5' X 2,500 lbs Cap. Distributed Weight
- 18" X 10' X 5,000 lbs Cap. Distributed Weight
- 21" X 5' X 5,000 lbs Cap. Distributed Weight
- 21" X 10' X 10,000 lbs Cap. Distributed Weight

More models available.

W.F. WELLS - MODEL F-16-3, Heavy Duty Horizontal Twin Post Semi Automatic Bandsaw

Specifications

Capacity.....	Rectangular at 90° 17" High x 20" Wide, Round at 90° 17" Diameter
Weight Capacity.....	5,000 lbs
Blade Speed	60-500 SFPM
Blade Size	1½" X .050" X 16' 8"
Blade Guide.....	Carbide with Roller Backup
Blade Tension.....	Hydraulic
Bandwheel Size	22"
Vise	Full Stroke Hydraulic
Blade Drive	10 HP, AC Vector Drive
Sawing Force.....	0-750 lbs
Coolant Capacity	15 Gallons
Hydraulic Capacity	20 Gallons
Hydraulic Drive	2 HP Motor
Work Height.....	35"
Shipping Weight.....	3,200 lbs
Electrics	Wired to NFPA 79 Machine Tool Standards
Machine Dimensions.....	50" Length x 101" Width x 88" Height

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Automatic Length Stop Assembly
- Discharge Worktable, 22" W x 48" L with Stock Stop
- Work Light, Wired In
- Blade Break/Stall Switch
- Hydraulic Chip Conveyor
- Hydraulic Holddown, Saw Vise
- Hydraulic Powered Conveyor 21" X 10'
- High Speed Drive & Guides (1¼" Blade) 400-3000 SFPM
- Free Standing Non-Powered Conveyors, 6" Centers

- 21" X 5' X 5,000 lbs Cap. Distributed Weight
- 21" X 10' X 10,000 lbs Cap. Distributed Weight

More models available.